

# Canterbury LED Oil RUSTIC

## Technical Data Sheet



**Staki** is a long established flooring producer situated in Lithuania. All products are made using a European top layer adhered to a birch plywood base. The boards are 2.4m in length and are substantial floors designed to last.

A strong earth undertone with a hint of silky grey, we welcome the **Canterbury** as a new member to our selection. The lightly brushed texture of the floor adds a new dimension to the depth of colour. A truly versatile colour, used to create both modern and rustic designs.



## RUSTIC GRADING DESCRIPTION

**Staki Rustic floors can contain the following:**

- Sound knots up to 90mm diameter
- Filled knots up to 50mm diameter
- Quantity of knots are not limited
- Small cracks on the surface of board
- All cracks and knots can be filled
- Natural colour variation

## FLOORING SPECIFICATION

Species	Oak
Grade	Rustic
Design	Plank
Construction	Engineered
Dimensions mm	220W x 20T x 2400L or 180W x 15T x 2400L
Wear Layer	6mm (20mm thick boards) or 4mm (15mm thick boards)
Bevels	2 (on long sides)
Surface Finish	LED Oil
Joint Type	Tongue & Groove
Base Layer	Birch Plywood
Warranty	25 years

## INSTALLATION

Acclimatisation	2 days on site
Humidity	30-65%
Underfloor Heating	Compatible
UFH Temperature	< 27°C
Installation Method	Fully bonded

\* Full installation guide available

## MAINTENANCE

Protection	Entrance matting/furniture feet
Daily Cleaning	Dry mop
Regular Cleaning	Osmo Wash & Care
Periodic Cleaning	Osmo Liquid Wax Cleaner

## PERFORMANCE CLASSIFICATION

- Reaction to fire: Dfl s1
- Lowest Average Density: 500kg m<sup>3</sup>
- Emissions of formaldehyde: E1 R.N. 635
- Content of pentachlorophenol: ≤ 5 ppm  
BS EN 14342:2013
- Breaking strength: NPD BS EN 14342:2013
- Slipperiness USRV: 43 R.N. 637
- Thermal conductivity: 0.16 W/mK  
R.N. 046/15-3
- Biological durability: 1 class  
BS EN 14342:2013