



Staki is a long established flooring producer situated in Lithuania. All products are made using a European top layer adhered to a birch plywood base. The boards are 2.4m in length and are substantial floors designed to last.

For those who would like the opportunity to create their own unique, perfectly designed floor, these unfinished planks come ready to receive any stain, oil or lacquer. The choice is up to you.



RUSTIC GRADING DESCRIPTION

Staki Rustic floors can contain the following:

- Sound knots up to 90mm diameter
- Filled knots up to 50mm diameter
- Quantity of knots are not limited
- Small cracks on the surface of board
- All cracks and knots can be filled
- Natural colour variation

FLOORING SPECIFICATION

Species	Oak
Grade	Rustic
Design	Plank
Construction	Engineered
Dimensions mm	220W x 20T x 2400L or 180W x 15T x 2400L
Wear Layer	6mm (20mm thick boards) or 4mm (15mm thick boards)
Bevels	2 (on long sides)
Surface Finish	Unfinished
Joint Type	Tongue & Groove
Base Layer	Birch Plywood
Warranty	25 years

INSTALLATION

Acclimatisation	2 days on site
Humidity	30-65%
Underfloor Heating	Compatible
UFH Temperature	< 27°C
Installation Method	Fully bonded

* Full installation guide available

MAINTENANCE

Protection	Entrance matting/furniture feet
Daily Cleaning	Dry mop

Oiled Floors

- **Regular Cleaning** - Osmo Wash & Care
- **Periodic Cleaning** - Osmo Liquid Wax Cleaner

Lacquered Floors

- **Regular Cleaning** - Bona Spray Mop for lacquered floors
- **Periodic Cleaning** - Bona Freshen Up

PERFORMANCE CLASSIFICATION

- Reaction to fire: Dfl s1
- Lowest Average Density: 500kg m³
- Emissions of formaldehyde: E1 R.N. 635
- Content of pentachlorophenol: ≤ 5 ppm BS EN 14342:2013
- Breaking strength: NPD BS EN 14342:2013
- Slipperiness USRV: 43 R.N. 637
- Thermal conductivity: 0.16 W/mK R.N. 046/15-3
- Biological durability: 1 class BS EN 14342:2013