## TECHNICAL INFORMATION SHEET



# CLA1006 Harris Oak Classic Collection



Additional Information

Responsible Certification UKTR Complicance

PEFC® Yes

#### **Product Information**

**Product Name Product Code** Collection Construction Size **Pack Size** Grade Surface **Finish Profile** Edge **Pattern** Width Lenath **Thickness Wear Layer Backing Top Layer** 

Harris Oak CLA1006 Classic Engineered 14 x 150 x RL 2.64m<sup>2</sup> Rustic Brushed **UV** Oiled 2G **Bevelled** Plank 150mm RL14mm 3<sub>mm</sub> **Poplar** Oak

### Installation and Warranty

A&K recommend all floors should be installed by a competent installer. A&K warranties apply only to floors that have been installed according to our fittings instructions found on our website.

Floated

Secret Nailed

Stuck Down

Underfloor F

### Installation Method

Floated Yes
Secret Nailed No
Stuck Down Yes
Underfloor Heating Yes

#### **Grading Information**

Rustic grade has the potential to include all characteristics across the majority of boards with knots appearing in varying sizes as well as colour variation in the timber to be expected. Sapwood is possible, checks that are likely to be present will be filled in a colour to complement the natural look of the timber.

#### **Technical Information**

Formaldehyde EmissionsE1Pentachlorophenol Emissions0.02-0.04mg/LThermal Conductivity0.1-0.12W/(M.K)Slip Resistance0.5-0.8Fire ClassificationDfl-s1Moisture Content6-8%Hardness Rating2H

This technical information sheet was compiled and written by Atkinson & Kirby. At the time of publication all information is specified correctly. The company reserves the right to change the specification of this product at any time without prior notice for third parties. To confirm the latest information please speak to a member of our team.