## TECHNICAL INFORMATION SHEET

## CLA1003 Lismore Oak Classic Collection



and the state of the second	Product Information	
all and the second	Product Name	Lismore Oak
- Index and a	Product Code	CLA1003
the state of the second	Collection	Classic
Contraction and the second	Construction	Engineered
Contraction of the second	Size	14 x 150 x 1900mm
Contraction of the second s	Pack Size	2.28m <sup>2</sup>
	Grade	Rustic
	Surface	Brushed
	Finish	UV Oiled
A CONTRACTOR OF THE OWNER OF THE OWNER OF	Profile	5G
	Edge	Bevelled
and the second	Pattern	Plank
	Width	150mm
	Length	1900mm
	Thickness	14mm
Additional Information	Wear Layer	3mm
Responsible Certification FSC®	= Backing	Poplar
UKTR Complicance Yes	Top Layer	Oak
Installation and Warranty	Installation Method	
A&K recommend all floors should be installed by a	Floated	Yes
competent installer. A&K warranties apply only to	Secret Nailed	No
floors that have been installed according to our fittings	Stuck Down	Yes
instructions found on our website.	Underfloor Heating	Yes
Grading Information	Technical Information	
Rustic grade has the potential to include all	Formaldehyde Emissions	E1
characteristics across the majority of boards with knots	Pentachlorophenol Emissions	Not Detectable
appearing in varying sizes as well as colour variation	Thermal Conductivity	0.14W/(M.K)
in the timber to be expected. Sapwood is possible,	, Slip Resistance	NPD
checks that are likely to be present will be filled in a	Fire Classification	Dfl-s1
colour to complement the natural look of the timber.	Moisture Content	7-10%
	Hardness Rating	3.7

reserves the right to change the specification of this product at any time without prior notice for third parties. To confirm the latest information please speak to a

member of our team.

Floors that define your space Tel: 01695 573234 | Scotland T: 01506 505030 | sales@akirby.co.uk | www.akirby.co.uk