



STAKI

MAINTENANCE

Grey Stone / Tobacco / Asphalt Grey



Top coat	Natural Oil.
Finish	Additional oiling is recommended after floor installation with <i>Osmo Polyx Hardwax Oil</i>
Resistance	Wine, cola, coffee, tea, oil, water.
Care and Frequency	<ul style="list-style-type: none"> • Do not clean the oiled floor the first three weeks after installation. • Regular floor cleaning with <i>Osmo Wash & Care</i>. • Periodic cleaning with <i>Osmo Liquid Wax Cleaner</i>.
Operating Conditions	Residential and commercial.

Natural / Extra White / Walnut / Ebony / Smoked



Top coat	Hardwax Oil.
Finish	Additional oiling is recommended with <i>Osmo Polyx Hardwax Oil</i>
Resistance	Wine, coffee, fruit juice, water.
Care and Frequency	<ul style="list-style-type: none"> • Regular cleaning of the floor using <i>Osmo Wash & Care</i>. • Periodic cleaning <i>Osmo Liquid Wax Cleaner</i>.
Operating Conditions	Residential and commercial.



BP Lacquer

Top coat	UV lacquer.
Finish	Finished product.
Resistance	Tea, oil, water.
Care and Frequency	<ul style="list-style-type: none"> • General cleaning with <i>Bona Cleaner</i>.
Operating Conditions	Residential and commercial.

