



## Technical Data Sheet

### Holt Horsford Brown Matt Lacquered

Product Ref: HOZHORS



#### Flooring Specification

Species:	Oak
Grade:	Rustic
Design:	Herringbone
Construction:	Engineered
Thickness:	14mm
Width:	130mm
Length:	725mm
Wear Layer:	2.5mm
Bevelled:	4 sides
Finish:	Matt Lacquer
Joint:	Click
Base Layer:	Spruce

#### Installation and Maintenance

Installation Method: Fully bonded to subfloor\*

Underfloor Heating: Yes, Maximum Temperature 27°C \*\*

Regular Cleaning: Bona Spray Mop, Bona Cleaner

Periodic Cleaning: Bona Freshen Up

-\* Installation method recommended by the manufacturer

-\*\* Temperature of top surface must never exceed 27°C

All Subject to compatible subfloor and correct installation

#### Description of Surface

- Classification of the surface layer according to EN 13489 Free class
- Healthy knots Acceptable, without limit
- Unhealthy knots with filling, scattered Acceptable, cracks up to 45mmx100mm, unhealthy up to 85mm
- Unhealthy holes from knots Acceptable up to 40 mm in diameter
- Bark pockets Acceptable
- Colour scheme of surface layer Varied
- Arrangement of fibres Varied
- Silver grains Acceptable, without limit
- Sapwood Acceptable, without limit
- Filling cracks in filled Acceptable up to 8 mm wide, up to 600mm length
- Biodegradation of surface layer Unacceptable

\* According to the EN 13489 standard, 3% of different grade than indicated is acceptable. The limits of characteristic features of the product concern the upper layer of the element. The knots' fillings, especially in case of brushed surfaces, can be characterized by gaps which are a deliberate effect of this kind of decorative surface. Measurement of wood characteristics

