# TECHNICAL INFORMATION SHEET



Westray Oak

# CLA1008 Westray Oak Classic Collection



#### **Product Information**

**Product Name** 

**Product Code** CLA1008 Collection Classic Construction Engineered 14 x 190 x 1900mm Size **Pack Size** 2.89m<sup>2</sup>Grade Super Rustic Surface Brushed **Finish UV** Oiled **Profile** 5G Edge **Bevelled** Plank **Pattern** Width 190mm Lenath 1900mm **Thickness** 14mm **Wear Layer** 3<sub>mm</sub> **Backing Poplar Top Layer** Oak

### Additional Information

**Responsible Certification** FSC® **UKTR Complicance** Yes

# Installation and Warranty

A&K recommend all floors should be installed by a competent installer. A&K warranties apply only to floors that have been installed according to our fittings instructions found on our website.

Floated

Secret Nailed

Stuck Down

Underfloor H

# Installation Method

Floated Yes
Secret Nailed No
Stuck Down Yes
Underfloor Heating Yes

#### **Grading Information**

Super Rustic grade is likely to contain all characteristics

across all boards with any size of knot and level of
colour variation in the timber to be expected. Expect to
see some sapwood as well as checks and filler used in a colour to complement these natural variances in most boards.

Formaldehyde Emissions
Pentachlorophenol Emiss
Thermal Conductivity
Slip Resistance
Fire Classification
Moisture Content

## **Technical Information**

Formaldehyde Emissions E1
Pentachlorophenol Emissions Not Detectable
Thermal Conductivity 0.14W/(M.K)
Slip Resistance NPD
Fire Classification Dfl-s1
Moisture Content 7-10%
Hardness Rating 3.7

This technical information sheet was compiled and written by Atkinson & Kirby. At the time of publication all information is specified correctly. The company reserves the right to change the specification of this product at any time without prior notice for third parties. To confirm the latest information please speak to a member of our team.