

# TECHNICAL INFORMATION SHEET



## PAR1008 Sloane Smoked Oak Parquet Collection



### Product Information

<b>Product Name</b>	Sloane Smoked Oak
<b>Product Code</b>	PAR1008
<b>Collection</b>	Parquet
<b>Construction</b>	Engineered
<b>Size</b>	11 x 70 x 500mm
<b>Pack Size</b>	1.68m <sup>2</sup>
<b>Grade</b>	Select
<b>Surface</b>	Smooth
<b>Finish</b>	Natural Oil Protect
<b>Profile</b>	T&G
<b>Edge</b>	Square Edged
<b>Pattern</b>	Block
<b>Width</b>	70mm
<b>Length</b>	500mm
<b>Thickness</b>	11mm
<b>Wear Layer</b>	3.6mm
<b>Backing</b>	Spruce Staves
<b>Top Layer</b>	Oak

### Additional Information

<b>Responsible Certification</b>	FSC® Mix
<b>UKTR Compliance</b>	Yes

### Installation and Warranty

A&K recommend all floors should be installed by a competent installer. A&K warranties apply only to floors that have been installed according to our fittings instructions found on our website.

### Installation Method

<b>Floated</b>	No
<b>Secret Nailed</b>	No
<b>Stuck Down</b>	Yes
<b>Underfloor Heating</b>	Yes

### Grading Information

Select grade is likely to contain some boards that have a higher number of knots than Prime, and you should also expect some of these knots to be larger in size. There is a possibility of some sapwood and small cracks and filler are likely to be present. A greater level of colour variation in the timber is to be expected.

### Technical Information

<b>Formaldehyde Emissions</b>	E1
<b>Pentachlorophenol Emissions</b>	Not Detectable
<b>Thermal Conductivity</b>	RT = 0,078 m <sup>2</sup> K/W
<b>Slip Resistance</b>	R10
<b>Fire Classification</b>	Cfl-s1 (fully glued down)
<b>Moisture Content</b>	7% (+/-2%)
<b>Hardness Rating</b>	34-41

This technical information sheet was compiled and written by Atkinson & Kirby. At the time of publication all information is specified correctly. The company reserves the right to change the specification of this product at any time without prior notice for third parties. To confirm the latest information please speak to a member of our team.