




Technical Data Sheet

Holt Coniston Pearl Matt Lacquered

Product Ref: HTCONIS

	Flooring Specification		
	Species:	Oak	
	Grade:	Rustic	
	Design:	Plank	
	Construction:	Engineered	
	Thickness:	14mm	
	Width:	180mm	
	Length:	2200mm	
	Wear Layer:	2.5mm	
	Bevelled:	4 sides	
	Finish:	Matt Lacquer	
	Joint:	T&G	
Base Layer:	Spruce		
Installation and Maintenance		Description of Surface	
Installation Method: Fully bonded*, Floated on underlay		• Classification of the surface layer according EN 13489 Free class	
Underfloor Heating: Yes, Maximum Temperature 27oc **		• Healthy knots Acceptable, without limit	
Regular Cleaning: Bona Spray Mop, Bona Cleaner		• Unhealthy knots with filling, scattered Acceptable, cracks up to 45mmx100mm, unhealthy up to 85mm	
Periodic Cleaning: Bona Freshen up, 6 Months		• Unhealthy holes from knots Acceptable up to 40 mm in diameter	
-* Installation method recommended by the manufacturer		• Bark pockets Acceptable	
-** Temperature of top surface must never exceed 27°C		• Colour scheme of surface layer Varied	
All Subject to compatible subfloor and correct installation		• Arrangement of fibres Varied	
		• Silver grains Acceptable, without limit	
		• Sapwood Acceptable, without limit	
		• Filling cracks in filled Acceptable up to 8 mm wide, up to 600mm length	
		• Biodegradation of surface layer Unacceptable	

* According to the EN 13489 standard, 3% of different grade than indicated is acceptable. The limits of characteristic features of the product concern the upper layer of the element. The knots' fillings, especially in case of brushed surfaces, can be characterized by gaps which a deliberate effect of this kind of decorative surface. Measurement of wood characteristics

