Technical Data

14 x 180mm 5G Engineered Oak



Board Construction:



Product Specification & Handling Information:

Board Depth:	14mm	Pack Size:	2.268m²
Board Width:	180mm	Pack Weight:	19.24kg
Board Length:	1800mm	Packs Per Pallet:	40

Board Detail:

Type of Board:	Engineered Wood Flooring		Fix System:	Valinge 5G LOC
Finish:	Lacquered	Natural Oil	Grade:	Rustic
Bevel Detail:	4V Bevel		Core Material:	Pine
Density of Finish: According to EN13489 Testing Brinell (EN1534)	Average Hardness 37 MPa		Janka Reading:	1360

Manufacturer Testing Standard:

Standard:	EN14342:2013 - Three-layer Flooring Board		
Reaction to Fire:	Dfl - s1	Formaldehyde:	E-1
Minimum Density:	500 kg/m³	Thermal Conductivity:	0.14 W/mK
Minimum Thickness:	10mm	Biological Stability:	NPD

Misc Items:

Residential Warranty:	15 Years			Commercial Warranty:	On Application
Oak Origin:	Europe			Manufacturered In:	Poland
Installation Type:	☑ Float	☑ Bond	✓ Nail	Underfloor Heating	Suitable *

 $^{^\}star$ Suitable for UFH if installed as floating floor with DPM underlay. - Manifold temp must not exceed 26°C

Key Features:















Accredditations:

