Technical Data

14mm T&G Chevron Oak





Product Photo:



Board Construction:





Product Specification & Handling Information:

Board Depth:	14mm
Board Width:	130mm
Board Length:	725mm
Pack Size:	0.610m²
Pack Weight:	5.31kg
Packs Per Pallet:	56

Manufacturer Testing Standard:

Standard:	EN14342:2013 - Three-layer Flooring Board	
Reaction to Fire:	Dfl - s1	
Minimum Density:	500 kg/m³	
Minimum Thickness:	14mm	
Formaldehyde:	E-1	
Thermal Conductivity:	0.14 W/mK	

Board Detail:

Type of Board:	Engineered Wood Flooring	
Finish:	Brushed & Matt Lacquered	
Bevel Detail:	4V Bevel	
Density of Finish: According to EN13489 Testing Brinell (EN1534)	Average Hardness 37 MPa	
Fix System:	T&G	
Grade:	Rustic	
Core Material:	Pine	
Janka Reading:	1360	

Misc Items:

Residential Warranty:	30 Years		
Commercial Warranty:	On Application		
Oak Origin:	Europe		
Manufactured In:	Poland / Ukraine		
Installation Type:	×	Float	
	V	Bond	
	V	Nail	
Underfloor Heating:	Suitable for underfloor heating provided it is fitted in accordance with manufacturers instructions - Manifold temp must not exceed 29°C		

Key Features:













Accreditations:



