TECHNICAL INFORMATION SHEET

CON3008 Aldwych Oak **Contemporary Collection**



		Thickness	18mm
Additional Information		Wear Layer	3mm
UKTR Complicance	Yes	Backing	Eucalyptus
		Top Layer	Oak

Installation and Warranty	Installation Method	
A&K recommend all floors should be installed by a	Floated	Yes
competent installer. A&K warranties apply only to	Secret Nailed	Yes
floors that have been installed according to our fittings	Stuck Down	Yes
instructions found on our website.	Underfloor Heating	Yes

Grading Information	Technical Information	
Rustic grade has the potential to include all	Formaldehyde Emissions	E1
characteristics across the majority of boards with knots	Pentachlorophenol Emissions	≤ 5 ppm
appearing in varying sizes as well as many levels of	Thermal Conductivity	0.13W/(M.K)
natural colour variation in the timber to be expected.	Slip Resistance	USVR 90
A varying amount of sapwood is possible, checks that	Fire Classification	Dfl-s1
are likely to be present will be filled in a colour to	Moisture Content	6-9%
complement the natural look of the timber.	Hardness Rating	1.8kn

This technical information sheet was compiled and written by Atkinson & Kirby. At the time of publication all information is specified correctly. The company reserves the right to change the specification of this product at any time without prior notice for third parties. To confirm the latest information please speak to a

member of our team.

Floors that define your space Tel: 01695 573234 | Scotland T: 01506 505030 | sales@akirby.co.uk | www.akirby.co.uk



Aldwych Oak

Contemporary

18 x 190 x 1900mm

Heavy Brushed & Undulating

CON3008

Engineered

2.17m²

UV Oiled

Bevelled

190mm

1900mm

Rustic

T&G

Plank

Product Information	
Product Name	

Product Code

Construction

Collection

Pack Size

Grade

Surface

Finish

Profile

Pattern

Width

Length

Edge

Size