

## Technical Data Sheet

## Holt Worcester Brown Matt Lacquered

## Product Ref: HO207WO

	Flooring Specification	
	Species:	Oak
	Grade:	Rustic
	Design:	Plank
	Construction:	Engineered
ALL YEAR ALL AL	Thickness:	14mm
	Width:	207mm
	Length:	2200mm
	Wear Layer:	3.2mm
	Bevelled:	4 sides
	Finish:	Matt Lacquer
	Joint:	Click
MAN THE CONTRACT THE	Base Layer:	Spruce
Installation and Maintenance	De	escription of Surface
Installation Method: Fully bonded*, Floated on underlay	<ul> <li>Classification of the surface layer according EN 13489 Free class</li> <li>Healthy knots Acceptable, without limit</li> <li>Unhealthy knots with filling, scattered Acceptable, cracks up to 45mmx100mm, unhealthy up to 85mm</li> <li>Unhealthy holes from knots Acceptable up to 40 mm in diameter</li> <li>Bark pockets Acceptable</li> <li>Colour scheme of surface layer Varied</li> <li>Arrangement of fibres Varied</li> <li>Silver grains Acceptable, without limit</li> <li>Sapwood Acceptable, without limit</li> </ul>	
Underfloor Heating: Yes, Maximum Temperature 27oc **		
Regular Cleaning: Bona Spray Mop, Bona Cleaner		
Periodic Cleaning: Bona Freshen Up		
-* Installation method recommended by the manufacturer		
-** Temperature of top surface must never exceed 27°c		
All Subject to compatible subfloor and correct installation	• Filling crack wide, up to	ks in filled Acceptable up to 8 mm 600mm length
	Biodegrada	tion of surface layer Unacceptable

\* According to the EN 13489 standard, 3% of different grade than indicated is acceptable. The limits of characteristic features of the product concern the upper layer of the element. The knots' fillings, especially in case of brushed surfaces, can be characterized by gaps which a deliberate effect of this kind of decorative surface. Measurement of wood characteristics

