

Technical Data

ProBond+

Professional Hardwood Flooring Adhesive

Product Photo:



Product Description:

- Environmentally friendly, free from solvents & moisture
- Flexible 'Advanced Hybrid Technology'
- Single component, ready to use
- Compatible with Underfloor Heating
- 13kg Unit



Technical Data:

Item code:	ACC-ADH-4338
Special Features:	<ul style="list-style-type: none"> • Elastically deformable • Excess adhesive easy to remove • Water and solvent-free, no wood swelling • Very well spreadable • Particularly suitable for multiple layer wood flooring
Suitable for installation of:	<ul style="list-style-type: none"> • Multiple layer wood flooring according to DIN EN 13489
Suitable Sub Floors:	<ul style="list-style-type: none"> • Calcium sulphate (flow) floors • Mastic asphalt screed, only after priming with STAUF VEP 195 • STAUF levelling compounds for wood flooring • Chipboards V100 (E1), OSB boards • Cement floors
Suitable primers:	<ul style="list-style-type: none"> • STAUF VDP 130 • STAUF VPU 155 S • STAUF VEP 195
Suitable leveling compounds:	<ul style="list-style-type: none"> • STAUF XP 40 • STAUF AS • STAUF XP 20 • STAUF GS • STAUF FZ • STAUF RM • STAUF PU • STAUF SSP RAPID

Product Properties:	<ul style="list-style-type: none"> • Aging-resistant • Suitable on sub floor heating systems • Not sensitive to frost • Fast setting
Colour:	• Beige
Required quantities per m ²	• 1150g with STAUF notched trowel no. 5
Open Time:	• Approx. 30 minutes at 20 °C
Accessibility:	• After approx. 48 hours
Room climate at work site:	• Minimum 15 °C, maximum 75% rel. humidity, preferably max. 65%
Shelf Life:	• 12 months
Giscode:	• RS 10
Emicode:	• EC1-R plus
Packaging:	• 13 kg plastic bucket

Key Features:

