

Technical Data Sheet

Lavish Opulence Select 15mm

Product Ref: SLBE180LACS



<u>Flooring Specification</u>	
Species:	Oak
Grade:	Select
Design:	Plank
Construction:	Engineered
Thickness:	15mm
Width:	180mm
Length:	2400mm
Wear Layer:	4mm
Bevels:	2
Finish:	Matt Lacquered
Joint:	T&G
Base Layer:	11.5mm Multilayer Birch

<u>Installation and Maintenance</u>
<p>Installation Method: Fully bonded*, Floated on underlay</p> <p>Underfloor Heating: Compatible with both electric and water based underfloor heating. Please check with UFH manufacturer before installation**</p> <p>Regular Cleaning: Bona Spray Mop, Bona Cleaner</p> <p>Periodic Cleaning: Bona Freshen Up, 6 Months</p> <p>-* Installation method recommended by the manufacturer</p> <p>-** Temperature of top surface must never exceed 27°C UFH Protocol to control temperature is recommended.</p> <p>All Subject to compatible subfloor and correct installation</p>

<u>Description of Surface</u>
<ul style="list-style-type: none"> • Healthy, cracked, not fallen out knots till 8-10 mm; • Rare occurred fallen out knots till 8 mm; • Rare occurred light timber color variation, white spots; • Knots are filled; • No sapwood.
<u>Performance Classification</u>
<ul style="list-style-type: none"> • Reaction to fire: Dfl s1 <ul style="list-style-type: none"> - Lowest Average Density 500kg m³ - Lowest Total Thickness – 15.5mm • Emissions of formaldehyde: E1 R.N. 635 • Content of pentachlorophenol: ≤ 5 ppm EN 14342:2013 • Breaking strength: NPD EN 14342:2013 • Slipperiness USRV: 43 R.N. 637 • Thermal conductivity: 0.16 W/mK R.N. 046/15-3 • Biological durability: 1 class EN14342:2013

* According to the EN 13489 standard, 3% of different grade than indicated is acceptable. The limits of characteristic features of the product concern the upper layer of the element. The knots' fillings, especially in case of brushed surfaces, can be characterized by gaps which a deliberate effect of this kind of decorative surface. Measurement of wood characteristics

