

Lavish Bespoke Lacquered

The Lavish Bespoke Lacquered collection is part of our beautiful lacquered range that is produced in a workshop in Surrey. The range consist of various colours and special treatments with a final application of hardwearing lacquer applied.

FLOORING SPECIFICATION

Species	Engineered Oak
Grade	Rustic
Design	Plank
Dimensions Available	220x20x2400mm 220x15x2400mm 180x15x2400mm
Wear Layer	6mm 220x20x2400mm 4mm 220x15x2400mm 180x15x2400mm
Bevels	2
Surface Finish	Lacquered
Joint Type	Tongue & Groove
Fitting Method	Fully Bonded or Floating

*Also available in select grade at request

PERFORMANCE CLASSIFICATION

- Reaction to fire: Dfl s1
- Lowest Average Density 500kg m3
- Emissions of formaldehyde: E1 R.N. 635
- Content of pentachlorophenol: ≤ 5 ppm BS EN 14342:2013
- Breaking strength: NPD BS EN 14342:2013
- Slipperiness USRV: 43 R.N. 637
- Thermal conductivity: 0.16 W/mK R.N. 046/15-3
- Biological durability: 1 class BS EN 14342:2013

INSTALLATION & MAINTENANCE

Installation Method: Fully bonded*, Floated on underlay

Underfloor Heating: Compatible with both electric and water based underfloor heating. Please check with UFH manufacturer before installation**

Regular Cleaning: Osmo Oil wash & Care

Periodic Cleaning: Osmo Liquid Wax Cleaner

* Installation method recommended by the manufacturer.

** Temperature of top surface must never exceed 27°C UFH Protocol to control temperature is recommended.

All Subject to compatible subfloor and correct installation. Please see Maintenance Sheet for more information.

DESCRIPTION OF SURFACE

- Sound not fallen out knots > 25 mm
- Open knots are filled
- Permitted fallen out knots > 25 mm
- Quantity of knots are not limited
- Small cracks on the surface of board
- All cracks and knots can be filled
- Natural colour variation including sapwood