


Product Photo:



Board Construction:



Product Specification & Handling Information:

Board Depth:	12mm
Board Width:	190mm
Board Length:	1900mm
Pack Size:	2.888m ²
Pack Weight:	22kg
Packs Per Pallet:	45

Manufacturer Testing Standard:

Standard:	EN14342:2013 - Multiply Flooring Board
Reaction to Fire:	Dfl - s1
Minimum Density:	620 kg/m ³
Minimum Thickness:	12mm
Formaldehyde:	E-1
Thermal Conductivity:	0.12 W/mK

Board Detail:

Type of Board:	Engineered Wood Flooring
Finish:	Brushed & Matt Lacquered
Bevel Detail:	4V Bevel
Density of Finish:	150g/m ²
Fix System:	Clic
Grade:	MAXC01
Core Material:	Multiply
Janka Reading:	NPD

Misc Items:

Residential Warranty:	15 Years
Commercial Warranty:	5 Years
Oak Origin:	Europe
Manufactured In:	PRC
Installation Type:	<input checked="" type="checkbox"/> Float
	<input checked="" type="checkbox"/> Bond
	<input checked="" type="checkbox"/> Nail
Underfloor Heating:	Suitable for UFH if installed as floating floor with DPM underlay. - Manifold temp must not exceed 26°C

Key Features:



Accreditations:

